



SUMMER MAY BE GONE BUT OUR FALL ATTACHMENT SPECIALS HAVE JUST ARRIVED!

FOR A LIMITED TIME, TAKE ADVANTAGE OF 35% OR MORE OFF SELECT ATTACHMENT BUNDLES.

SPECIAL

AUGER BUNDLES

PURCHASE SELECT
AUGER DRIVES, MOUNTS
AND BIT AT **35% OFF**
+ RECEIVE A FREE
10" OR 15" HEX
EARTH AUGER!

PURCHASE 3 OR
MORE BUNDLES TO
SAVE EVEN MORE
WITH **FREE SHIPPING!**

PRODUCT SPECIFICATIONS	SKID STEER LOADERS (Up to 80HP)		MINI EXCAVATORS 1T TO 3T		EARTH DRILLS // MINI LOADERS	
	Model	3300-30	X2100-17	X1600-15	ML2100-17	ML1600-15
Oil Pressure Range	1161 - 3481 psi	1016 - 3481 psi	1016 - 3481 psi	1016 - 3481 psi	1016 - 3481 psi	1016 - 3481 psi
Torque Range	1107 - 3319 ft-lb	612 - 2100 ft-lb	472 - 1616 ft-lb	612 - 2100 ft-lb	472 - 1616 ft-lb	472 - 1616 ft-lb
Oil Flow Range	13 - 30 gpm	7 - 17 gpm	6 - 15 gpm	7 - 17 gpm	6 - 15 gpm	6 - 15 gpm
Speed Range	42 - 97 rpm	36 - 87 rpm	40 - 99 rpm	36 - 87 rpm	40 - 99 rpm	40 - 99 rpm
Hub Options	2" Hex (STD) 2.25" Square 2.56" Round	2" Hex (STD) 2.25" Square 2.56" Round	2" Hex (STD) 2.25" Square 2.56" Round	2" Hex (STD) 2.25" Square 2.56" Round	2" Hex (STD) 2.25" Square 2.56" Round	2" Hex (STD) 2.25" Square 2.56" Round
Height	26 in.	23 in.	23 in.	19 in.	18 in.	
Width	10 in.	8 in.	8 in.	8 in.	8 in.	
Weight	166 lbs	106 lbs	104 lbs	86 lbs	86 lbs	
Hitch Options	Single Pin Hitch Double Pin Hitch Cradle Hitch	Single Pin Hitch Double Pin Hitch Cradle Hitch	Single Pin Hitch Double Pin Hitch Cradle Hitch	Mounting Frame: 2 Way Swing 4 Way Swing	Mounting Frame: 2 Way Swing 4 Way Swing	
Auger Range	S4	S4	S4	S4	S4	
Rec. Drilling Diameter Range	4" to 36"	4" to 20"	4" to 18"	4" to 20"	4" to 18"	

SPECIAL

TRENCHER BUNDLES

PURCHASE SELECT
TRENCHERS, MOUNTS &
CHAINS AT DISCOUNTS
TOO GOOD TO ADVERTISE

PRODUCT SPECIFICATIONS	EXCAVATORS 3 - 5T & SKIDSTEER LOADERS (For trenches 4-12 in. width)	
	Model	MT 36
Oil Pressure Range	2610-3481 psi	2610-3481 psi
Oil Flow Range	12-25 gpm	12-27 gpm
Unit Height	2 ft. 5 in.	2 ft. 5 in.
Unit Width	2 ft. 9 in.	2 ft. 9 in.
Unit Length	5 ft. 10 in.	6 ft. 10 in.
Cutting Width Range	4-12 in.	4-8 in.



Connect with us via



augertorqueusa.com 844.287.6300

